

MCG GRONDEER MIDDEL

Composition

MCG Grondeer Middel, is a water based strengthened and sealant impregnation based on acrylic emulsions, organic solvent free and exempt of bituminous products. Low water absorption, forms superficial film.

Uses

MCG Grondeer Middel is developed for surface preparation, specially designed to consolidate and seal required supports. Also to optimize the adherence or compaction of supports.

Security & Hygiene

MCG Grondeer Middel is not toxic, hazardous or flammable in normal handling conditions. It's recommended a usage with no specific security action, only the legal health labour norms.

Presentation

5l Jerrycan
1,15 x 1,15 Pallet ---- 144 units



Technical features

Dry to the touch:	1 hour
Frost stability:	Good
Repainting:	12 hours
Outdoor resistance:	Aliphatic, UV resistant
Saponification resistance:	Good
Adherence:	Good on absorbent supports
Finish:	Glossy according performance
Recommended thickness:	50 um
Output:	+/- 20m ² /kg. According the surface.
Dry to the touch:	1 hour

Storage

Must be stored between 5 and 40 °C in its original package. Do not store over 12 months.

Dilution

Ready to use.

According porosity, nature and features of the support, as well as the finishing product requirements, can be diluted in a large range. WATER: 1/2, 1/3, 1/4, 1/5.